


CIRCUIT



主要技术参数、性能

The Main Thchnology Performance

|                                 |                                |
|---------------------------------|--------------------------------|
| 额定电流、电压<br>Rate voltage current | 12V DC,50mA                    |
| 接触电阻<br>Contact resistance      | ≤100mΩ . MAX                   |
| 操作力<br>Operating force          | 180 ± 50 gf<br>for 250 ± 50 gf |
| 耐焊规格<br>Solder Specifications   | 260°C for<br>3 Seconds         |
| 绝缘电阻<br>insulated resistance    | ≥100mΩ . MIN                   |
| 寿命<br>Endurance                 | 200,000 cycles                 |
| 使用温度<br>Service temperature     | -20°C to 70 °C                 |
| 总行程<br>TOTAL TRAVEL             | 0.25±0.1mm                     |

| E          |                   |                |           |                        |
|------------|-------------------|----------------|-----------|------------------------|
| D          |                   |                |           |                        |
| C          |                   |                |           |                        |
| B          |                   |                |           |                        |
| A          |                   |                |           |                        |
| 项目<br>ITEM | 名称<br>DESCRIPTION | 材质<br>MATERIAL | 数量<br>QYT | 表面处理/颜色<br>FINSH/COLOR |

|             |                 |                   |                |              |             |                           |       |  |  |
|-------------|-----------------|-------------------|----------------|--------------|-------------|---------------------------|-------|--|--|
|             |                 |                   |                |              |             | 第一视角<br>FIRST VIEW        |       | 名称/NAME:<br>带灯开关<br>ILLUMINATED TACT SWITCH SERIES |  |
|             |                 |                   |                |              |             |                           |       | 型号/MODEL:<br>TS01-1L<br>(Switch LED)               |  |
| 标记<br>SING  | 处数<br>FREQUENCY | 更改文件号<br>REVISION | 签名<br>APPROVED | 日期<br>DATE   | 标尺<br>SCALE | 一般公差<br>GENERAL TOLERANCE |       |  |  |
| 设计 DESIGN   |                 | Zhaoming          |                | 单位<br>UNIT   | mm          | 0.5~2                     | ±0.10 |  |  |
| 审核 CHECKED  |                 | Zengyong          |                | 重量<br>WELGHT |             | 2~5                       | ±0.15 |  |  |
| 批准 APPROVED |                 | Fuyunfeng         |                | 角度<br>ANGLE  |             | 5~10                      | ±0.20 |  |  |
|             |                 |                   |                |              |             |                           |       | ±0.5°  |  |