



主要技术参数、性能

The Main Thchnology Performance

额定电流、电压 Rate voltage current	DC 30V 0.5A
接触电阻 Contact resistance	≤100mΩ
绝缘电阻 insulated resistance	≥100mΩ DC 500V
耐受电压 Withstand Voltage	AC 500V (50-60HZ)1min
电寿命 Electrical Life	5000 Cycles
使用温度 Service temperature	-25°C+ 80 °C
使用湿度 Ambient humidity used	≤85%RH
耐焊温度 Withstand Soldering temperature	260°C ± 5°C 5S ± 1S

P.C.B LAYOUT TOP VIEW

E				
D				
C				
B				
A				
项目 ITEM	名称 DESCRIPTION	材质 MATERIAL	数量 QYT	表面处理/颜色 FINSH/COLOR

第一视角 FIRST VIEW						名称/NAME: 耳机插座 PHONE JACK SERIES			
标记 SING						型号/MODEL: PJ-309A			
处数 FREQUENCY		更改文件号 REVISION		签名 APPROVED		日期 DATE		比列 SCALE	
设计 DESIGN		Zhaoming				单位 UNIT		mm	
审核 CHECKED		Zengyong				重量 WELGHT		0.5~2 ±0.10	
批准 APPROVED		Fuyunfeng				角度 ANGLE		2~5 ±0.15	
								5~10 ±0.20	
								±0.5°	

