



PCB LAYOUT

主要技术参数、性能
The Main Thchnology Performance

额定电流、电压 Rate voltage current	See detail spec
接触电阻 Contact resistance	30m Ω Max
绝缘电阻 insulated resistance	100m Ω Min
耐受电压 Withstand Voltage	AC 500V (50-60HZ)1min
电寿命 Electrical Life	5000 Cycles
使用温度 Service temperature	-25 $^{\circ}$ C+80 $^{\circ}$ C
使用湿度 Ambient humidity used	\leq 85%RH
耐焊温度 Withstand Soldering temperature	260 $^{\circ}$ C \pm 5 $^{\circ}$ C 5S \pm 1S

E				
D				
C				
B				
A				
项目 ITEM	名称 DESCRIPTION	材质 MATERIAL	数量 QYT	表面处理/颜色 FINSH/COLOR

					第一视角 FIRST VIEW			名称/NAME: USB/TYPE-C	
								型号/MODEL: USB AM 沉板 SMT US01-025	
标记 SING	处数 FREQUENCY	更改文件号 REVISION	签名 APPROVED	日期 DATE	比列 SCALE		一般公差 GENERAL TOLERANCE		
设计 DESIGN		Zhaoming			单位 UNIT	mm	0.5~2	\pm 0.10	
审核 CHECKED		Zengyong			重量 WELGHT		2~5	\pm 0.15	
批准 APPROVED		Fuyunfeng					5~10	\pm 0.20	
							角度 ANGLE	\pm 0.5 $^{\circ}$	

